

FIG. 1




FIG. 2

09112786-071098




FIG. 3




FIG. 3(a)




FIG. 4

[illegible]

FIG. 5

09112786 "071098




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

09112785-071098




FIG. 15




FIG. 16

ORDER OF PIXELS PRESENTED BY A SEQUENTIAL READ ITERATOR
ON A 4 X 2 IMAGE WITH PADDING.

0	1	2	3	
4	5	6	7	

FIG. 17






FIG. 18

A 3x3 BOX VIEW TRAVERSES THE PIXELS IN ORDER: 0,1,2,3,4,5,6,7,8 ETC,
PLACING A 3x3 BOX CENTERED OVER EACH PIXEL...


3x3 BOX VIEW OF FIRST PIXEL IN
IMAGE = 9 PIXELS, 5 OF WHICH
ARE OUTSIDE THE IMAGE




150




FIRST 9 PIXELS FROM THE
BOX READ ITERATOR:



3x3 BOX VIEW OF SECOND PIXEL IN
IMAGE = 9 PIXELS, 3 OF WHICH
ARE OUTSIDE THE IMAGE



155
156



SECOND 9 PIXELS FROM THE
BOX READ ITERATOR:




FIG. 19





FIG. 20


IMAGE BROKEN INTO VERTICAL STRIPS, EACH STRIP IS 32 PIXELS ACROSS.



169


170

LINES ARE ACCESSED LINE 0 TO LINE N WITHIN A SINGLE STRIP.



166

PIXELS ARE ACCESSED PIXEL 0-PIXEL 31 WITHIN A SINGLE LINE.



167

165

FIG. 21

09112786 071098




FIG. 22




FIG. 23




FIG. 24

09112786 071098




FIG. 25





FIG. 26



2x2 PIXEL BLOCK FROM CCD

FIG. 27




FIG. 28





FIG. 29



2x2 PIXEL BLOCK FROM CCD

FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36

09112786 071098




FIG. 37




FIG. 38




FIG. 39




FIG. 40






FIG. 41






FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48

09112786 071098




FIG. 49





FIG. 50




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57

00:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	} 32 COPIES OF THE 3 BYTE CONTROL INFORMATION
0C:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
18:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
24:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
30:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
3C:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
48:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	
54:	4F 00 3D 4F 00 3D 4F 00 3D 4F 00 3D	} RESERVED BYTES ARE 0
60:	00 00 00 00 00 00 00 00 00 00 00 00	
6C:	00 00 00 00 00 00 00 00 00 00 00 00	
78:	00 00 00 00 00 00 00 00 00 00 00 00	

FIG. 59




FIG. 58




FIG. 60




FIG. 61




FIG. 62




FIG. 63

09112786 "071098




FIG. 64






FIG. 65



PROBABILITY OF A SYMBOL BEING IN ERROR DURING A READ

FIG. 66



APPROXIMATE DATA SIZES FOR 1600 DPI DOTCARD

86MM + 1MM IN HORIZONTAL DIMENSION FOR P ROTATION = 87MM

87MM = 16,252 SCANLINES

16,440 SCANLINES @ 11,000 PIXELS PER SCANLINE = 180,840,000 PIXELS

180,840,000 PIXELS @ 1 BYTE PER PIXEL = 180,840,000 BYTES = 172.5 MB

64 DATA BLOCKS, EACH CONTAINING 597 COLUMNS (595 DATA REGION COLUMNS AND 2 ORIENTATION COLUMNS), @ 48 BYTES PER COLUMN = 28,656 BYTES PER DATA BLOCK FOR A TOTAL OF 1,833,984 BYTES.

64 DATA BLOCKS, EACH CONTAINING 112 ENCODED REED SOLOMON BLOCKS, @ 255 BYTES PER REED SOLOMON BLOCK FOR A TOTAL OF 1,827,840 BYTES.

DECODED DATA, WITH A MAXIMUM SIZE OF 910,082 BYTES. (64 X 112 X 127 - (2 CONTROL BLOCKS @ 127 BYTES))

FIG. 67

09112786 071098




FIG. 68




FIG. 69




FIG. 70




FIG. 71




FIG. 72

09112786-071093

09412786 "071098




FIG. 73




FIG. 74

LOCATED TARGETS

0
NULL
...
NULL

POSSIBLE TARGETS

0
NULL
...
NULL


AVAILABLE TARGETS

28
...
TARGET 27

TARGET
STRUCTURES



FIG. 75



$$\text{Lanczos } 3(x) = \begin{cases} \frac{\sin(\pi x)}{\pi x} \frac{\sin\left(\frac{\pi}{3}\right)}{\frac{x}{\pi/3}}, & |x| < 3 \\ 0, & |x| \geq 3 \end{cases}$$

FIG. 76




FIG. 77

09112786-071098




FIG. 78




FIG. 79

09412786-074098




FIG. 80




FIG. 81




FIG. 82




FIG. 83




FIG. 84




FIG. 85




FIG. 86




FIG. 87




FIG. 88




FIG. 89

POINT (x,y) ON LEVEL B
OF PYRAMID




FIG. 90




FIG. 91




FIG. 92






FIG. 93






FIG. 95




FIG. 96




FIG. 97




FIG. 98




FIG. 99






FIG. 100






FIG. 104




FIG. 105




FIG. 106




FIG. 107




FIG. 108




FIG. 109




FIG. 110







FIG. 111






FIG. 112







-  LINEAR INTERPOLATED
PIXELS
-  BI-LINEAR INTERPOLATED
PIXELS
-  ACTUAL PIXELS (NOT
INTERPOLATED)

FIG. 113






-  LINEAR INTERPOLATED
PIXELS
-  BI-LINEAR INTERPOLATED
PIXELS
-  ACTUAL PIXELS (NOT
INTERPOLATED)

FIG. 114





FIG. 115





FIG. 116




FIG. 117




FIG. 118




FIG. 119




FIG. 120




FIG. 121




FIG. 122




FIG. 123




FIG. 124




FIG. 125




FIG. 126




FIG. 127




FIG. 128




FIG. 129




FIG. 130




FIG. 131




FIG. 132




FIG. 133




FIG. 134




FIG. 135




FIG. 136




FIG. 137




FIG. 138




FIG. 139




FIG. 140




FIG. 141




FIG. 142




FIG. 143




FIG. 144




FIG. 145

09442786, 071098




FIG. 146




FIG. 147




FIG. 148




FIG. 149

The flowchart illustrates a ray-tracing algorithm for global illumination, including direct and indirect lighting calculations. The process begins with three parallel input blocks: "BUMP-MAP SEQUENTIAL READ ITERATOR1", "BUMP-MAP SEQUENTIAL READ ITERATOR2", and "BUMP-MAP SEQUENTIAL READ ITERATOR3". These feed into a central circle labeled "CALCULATE N".

"CALCULATE N" outputs three signals: x_N , y_N , and z_N . x_N and y_N feed into "CALCULATE N·L", while z_N feeds into "CALCULATE R·V". "CALCULATE N·L" also receives feedback from "CALCULATE L" via signals x_L , y_L , and z_L . "CALCULATE R·V" receives feedback from "CALCULATE N·L" via x_L and y_L .

"CALCULATE N·L" feeds into "CALCULATE R·V", which then feeds into "CALCULATE SPECULAR 2". "CALCULATE SPECULAR 2" also receives input from the "IMAGE SEQUENTIAL READ ITERATOR". "CALCULATE SPECULAR 2" outputs to a summation node (+), which also receives input from "CALCULATE AMBIENT".

"CALCULATE SPECULAR 2" also feeds into "CALCULATE DIFFUSE 2", which receives input from "CALCULATE R·V". "CALCULATE DIFFUSE 2" outputs to another summation node (+), which also receives input from "CALCULATE AMBIENT".

"CALCULATE DIFFUSE 2" feeds into a multiplication node (*), which also receives input from a gain block K_3 . The output of this multiplication node feeds into a third summation node (+), which also receives input from "CALCULATE AMBIENT".

"CALCULATE DIFFUSE 2" also feeds into "CALCULATE f_{att}", which then feeds into another multiplication node (*). This multiplication node also receives input from a gain block K_3 . The output of this multiplication node feeds into a fourth summation node (+), which also receives input from "CALCULATE AMBIENT".

"CALCULATE f_{att}" also feeds into "CALCULATE L", which receives input from a gain block K_1 and a gain block K_2 . "CALCULATE L" outputs x_L , y_L , and z_L back to "CALCULATE N·L".

The final output of the algorithm is the "OUT-IMAGE SEQUENTIAL WRITE ITERATOR", which receives input from the fourth summation node (+). A dashed box encloses the "OUT-IMAGE SEQUENTIAL READ ITERATOR" and the fourth summation node (+), indicating a feedback loop for subsequent iterations.

A legend at the bottom right indicates that the dashed box represents the "2ND AND SUBSEQUENT LIGHTS".

☐ 2ND AND
SUBSEQUENT
LIGHTS





FIG. 151


09112785 "071098



8 PRINT HEAD SEGMENTS IN PRINT HEAD

SEGMENT 0	SEGMENT 1	SEGMENT 2	SEGMENT 3	SEGMENT 4	SEGMENT 5	SEGMENT 6	SEGMENT 7
-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------

1250 μ M
(375 DOTS PER SEGMENT ROW, OR 750 DOTS PER SEGMENT)



1 DOT IS 16.6 μ M IN DIAMETER
(A 100 μ M SQUARE = 6 X 6 = 36 DOTS)

466.6 μ M
(28 DOTS)

33.3 μ M
(2 DOTS)

133.3 μ M
(8 DOTS)

EACH SEGMENT CONTAINS 6 ROWS OF DOTS: ODD AND EVEN
CYAN, MAGENTA, AND YELLOW.

FIG. 153




FIG. 154







FIG. 155


6 DOTS = 100μ M



1 PIXEL = 6 X 6 DOTS
= 36 DOTS
= 100μ M SQUARE

FIG. 156









FIG. 160






FIG. 162

09112786.071098




FIG. 163




FIG. 164





FIG. 165

09112785 "071098




FIG. 166




FIG. 167




FIG. 168




FIG. 169




FIG. 170




FIG. 171




FIG. 172




FIG. 173




FIG. 174




FIG. 175




FIG. 176




FIG. 177

FIG. 178




FIG. 179




FIG. 180




FIG. 181

The diagram illustrates a memory map with the following components:

- Start Address:** 0 0000 0000
- Constants (16):** Address range 0 0000 0000 to 0 0001 0000.
- Reserved (48):** Address range 0 0001 0000 to 0 0100 0000.
- RAM (32):** Address range 0 0100 0000 to 0 0110 0000.
- Flash (32):** Address range 0 0110 0000 to 0 1000 0000.
- Program (384):** Address range 0 1000 0000 to 1 1111 1111.

Data Entry Sizes:

- 32-bit data entries:** Constants (16), Reserved (48), RAM (32), and Flash (32).
- 8-bit data entries:** Program (384).

FIG. 182




FIG. 183

09442786 074098

Start Address

0 0100 0000

E
D
C
B
A
T
H ₄
H ₃
H ₂
H ₁
H ₀
B160 ₄
B160 ₃
B160 ₂
B160 ₁
B160 ₀

A-E

Temp

H₀₋₄

B160₀₋₄

Start Address

0 0101 0000

X ₁₅
X ₁₄
X ₁₃
X ₁₂
X ₁₁
X ₁₀
X ₉
X ₈
X ₇
X ₆
X ₅
X ₄
X ₃
X ₂
X ₁
X ₀

X₀₋₁₅

FIG. 184




FIG. 185

034436-071098




FIG. 186




FIG. 187




FIG. 188

09412786 074098




FIG. 189




FIG. 190




FIG. 191




FIG. 192




FIG. 193




FIG. 194




FIG. 195




FIG. 196




FIG. 197




FIG. 198




FIG. 199




FIG. 200




FIG. 201




FIG. 202





FIG. 203

705



Data Type	Bits
Factory code	16
Batch number	32
Serial number	48
Manufacturing date	16
Media length	24
Media type	8
Preprinted media length	16
Cyan ink viscosity	8
Magenta ink viscosity	8
Yellow ink viscosity	8
Cyan drop volume	8
Magenta drop volume	8
Yellow drop volume	8
Cyan ink color	24
Magenta ink color	24
Yellow ink color	24
Remaining-media length indicator	16
Authentication key	128
Copyrightable bit pattern	512
Reserved for camera use	88
Total	1024

728



FIG. 204

SECRET




FIG. 205




FIG. 206




FIG. 207




FIG. 208




FIG. 209

SECTION 832




FIG. 210

870




FIG. 211




FIG. 212




FIG. 213


[illegible]

FIG. 214




FIG. 215




FIG. 216






FIG. 217



960720" 9822T60




FIG. 220




FIG. 221




FIG. 222




FIG. 223




FIG. 224




FIG. 225






FIG. 226








FIG. 229




FIG. 230




FIG. 231